

ELECTRONIC MAGNETO TELEPHONE DESK TYPE



INTRODUCTION :

The Electronic Magneto Telephone Desk Type is designed to meet communication requirements in Railways and similar set-ups, in between two or more stations. It is fully solid-state and works on 1.2Vx3 rechargeable cells. Alternately, it can be connected to an external 3V Battery. A push button switch is used to alert the party at the other end by giving a buzzer tone, two beeps can be used by pressing twice when using in between more than two stations. A side tone is also heard in the Telephone of the sending station. The indications for the incoming ring is given by a green LED on the telephone housing. This is designed to replace Conventional Magneto Telephone with hand cranking, generator thus named as Electronic Magneto Telephone. (Mainly Follows Electrical parameters as per IRS:TC-79/2000 of Indian Railways.)

SPECIFICATIONS :

Operating Voltage	:	3V +20%, - 10%
Current Consumption	:	20mA at 3V.
Power Source	:	External Battery 3V.
Ringer Source	:	AC Buzzer.
Transducers	:	Electro dynamic-RT 200
Telephone Housing	:	Siemens Type
Handset Chord	:	4 Coiled.
Line Chord	:	2 Conductors.
Working range for Ringer and conversation	:	65 Kms.

Provided with Battery charger/ adaptor

TECHNICAL DATA SHEET 79 Rev- 25-12-2015



ANU VIDYUT

C-1, INDUSTRIAL ESTATE ROORKEE - 247 667
Tel: (01332) – 262545,268040 Fax: (01332)-260869
E-mail:info@anuvidyut.com / anuvidyut@gmail.com

